

# BASE SPECIFICATION GUIDE SIGNATURE SERIES 2” PVC FASHIONS PLUS BLINDS

## PART I- GENERAL

### 1.01 REQUIREMENTS

- A. Provide and install **Signature Series Blinds** manufactured by **CACO, Inc.** in agreement with all specifications, drawings and contract correspondence.
- 

### 1.02 SUBMITTALS

- A. Provide manufacture’s product data and installation information per type of blind specified.
- 

## PART II - PRODUCTS

### 2.01 HORIZONTAL MAXI BLINDS

- A. **CACO, Inc.** custom **Signature Series/2” PVC Fashions Plus** horizontal blinds.

#### B. Materials

1. **Signature Series/ 2” PVC Fashions Plus** head rail is a “U” shaped configuration: dimensions are 2” high by 2 1/4” deep, with rolled edges at the top. Fabricated steel is 0.024-inch thick (before paint) and iron phosphate treated. Head rail is acrylic primed with a finish coat of baked on polyester enamel.

- a. Head rail shall incorporate a steel end brace with an adjustable tab for reinforcement

2. **Operating hardware** is of a snap in design and positioned to allow precise alignment.

3. **Tape roll supports and tape rolls: 2” PVC**

**Fashions Plus (Braided Ladder)** tape roll supports are made of low friction thermoplastic, which are self lubricating and maintenance free for smooth operation and diminished wear on lift cords and braided ladders. The support also provides the tape roll with smooth bearing points and centers it over the ladder guide hole. Tape rolls are constructed of low friction thermoplastic and designed to hold tape end by

means of a “U” shaped brass grommet, which shall be inserted into tape rolls, allowing for a more precise placement of ladders when secured. As a result this gives the top slat a near level bearing position. Tape rolls shall include a projecting thermoplastic cylindrical collar integrated on each end, tilt rod is centered through both tape drum and collar projection. Self-lubricating thermoplastic collars are designed to snap securely into tape drum supports allowing for a near effortless tilting operation. **2” Fashions Plus (Cloth Tapes)** tape roll supports and tape rolls are constructed of thermoplastic. Tape roll supports utilize a nylon pulley system to guide lift cords through head rail. **2” Fashions Plus (Cloth Tapes)** tape rolls are designed to hold cloth or vinyl tape ends firmly by means of stapled loops and provides a full tilting action.

4. **Crash-proof cord lock:** This component shall be a snap-in design and has a nylon roller, which the cord smoothly passes over. A secured steel roller onto a hinged lock facilitates “crash-proof” feature. Locking mechanism secures the blind the cord is released. The cord ends are knotted and are made of low friction thermoplastic, which are equipped with color coordinated cord tassels.

- a. An optional lift cord ring pull is available in lieu of cord tassels and shall be supplied with a standard 4-inch control length.

5. **Tilters: 2” PVC Fashions Plus** is available with either standard cord tilter or optional wand tilter. The highly accurate cord tilter utilizes a corrosion resistant steel worm and gear system, enclosed in a high impact plastic body which incorporates a spool protector that prevents the cord from slipping off of the spool. The cords operate smoothly by an incorporated pulley and cord guide. The optional wand tilter is a precise, self-lubricating thermoplastic worm and gear mechanism, with a fully enclosed plastic housing. Both precise tilter systems are designed to hold slats at any angle without movement. Color coordinated wood tassels are provided with cord tilt.

- a. Optional tilt ring shall be attached to the tilter shaft in lieu of a wand, allowing for the field provision of a pole hook to operate.

6. **Tilt wand: 2” PVC Fashions Plus** wand is composed of clear plastic, which is hexagonal in shape and measures 3/8-inch across.. Wand shall be attached or detached to tilter shaft via a metal clip which is secured to the wand section.

7. **Tilt rod:** This component, square in shape, is composed of solid galvanized steel and provides an instant tilting response. Diameter measurement across is 1 /4inch.

8. **2” PVC Slats:** Standard curved 2-inch width vinyl (PVC poly-vinyl chloride) smooth edged slats, shall be composed of virgin Geon pellets and extruded to a thickness of 0.040 gauges (±.0003). Both smooth solid colors and embossed styles in colors are available.

9. **Bottom rail** is fully enclosed, and shall be made of roll formed steel, sculptured in design for maximum strength. The fully enclosed steel bottom rail is 0.024inch thick. Bottom rail is phosphate treated, acrylic primed, with a finish coat of baked on polyester enamel to color coordinate with head rail and end brackets.

- a. Thermoplastic end caps are color coordinated with bottom rail.

- b. Tape retainers are fabricated from corrosion resistant steel and have a finish coat to color coordinate with bottom rail.

10. **Tapes and ladders (ladder tape):** Standard color coordinated braided ladders shall be constructed of polyester yarn with a double crossed inter-braided cable thread design, for maximum slat support and minimum stretch. Slats shall be supported by ladder tape without any visible distortion. Ladder rung distances shall not exceed 44 mm (6.9 slats per vertical foot). Distances between ladders shall not exceed 20-inches, nor shall distance from end of ladder to end of slat not exceed 6 – inches. **Optional** 1 ½” and 1” cloth tapes (in varying colors) are constructed of high strength polyester. Spacing shall not exceed 42 mm.

- a. Optional 1 ½" vinyl tapes are available.
11. **Lift cords:** Color coordinated lift cords shall be constructed of a braided polyester jacket with a rayon center core or approved equal. Cords shall be of sufficient length to properly facilitate the raising and lowering of blind. Diameter of cord shall be 1.8 mm (+-0.1 mm).
12. **End support bracket:** Galvanized steel installation bracket with riveted hinged cover shall be 0.038-inch thick (before paint). The outside surface has a finish coat of baked polyester enamel to color coordinate with head rail, slats and bottom rail.
- a. Intermediate support brackets are furnished for blinds 48-inches wide or as required. Maximum spacing for brackets shall be 30-inches.
- b. Optional extension brackets are available.
13. **Packaging:** Corrugated 44 ECT cardboard packaging consists of 100% recycled material that is also 100% recyclable (a letter of compliance is on file for LEED qualifying projects).
14. **General: Signature Series 2" PVC Fashions Plus** shall be manufactured exempt of any sharp edges, burrs or other defects. **CACO, Inc.** will extend a limited life warranty on **2" PVC Fashions Plus** head rail and components and a 3-year warranty on slats. Every horizontal blind that is properly installed is guaranteed to be free from defective components for the warranty duration, as long as the blind remain in the same window as originally installed. This obligation is limited to repair and replacement of components found defective. This guarantee does not include any conditions resulting from damages caused by accidents, alterations, misuse, abuse, or failure to follow instructions with respect to cleaning or maintenance.
15. **Size limitations:**
- a. Maximum width: 96-inches
- b. Maximum length: 108-inches

---

## 2.01 FABRICATION

- A. Prior to fabrication, verify actual opening sizes by measuring on site. Calculate blind dimensions to fit within specified tolerances.
- B. Fabricate blinds to fill opening from top of window to sill and jamb to jamb. The minimum clearance blind to blind shall be 1/4-inch. Locate blind divisions at mullions.

---

## PART III - EXECUTION

### 3.01 INSPECTION

- A. Work area in which blinds will be installed should be free of conditions that interfere with blind installations and operations. Begin blind installation only when unsatisfactory conditions have been corrected.

---

### 3.02 INSTALLATION

- A. Install blinds in accordance with manufacture's installation procedures except as otherwise specified.
- B. Install intermediate support brackets and extension brackets as needed to prevent deflection in head rail.
- C. Install blinds with adequate clearance to permit smooth operation of blinds and any sash operations. Hold blinds 1/4-inch clear from each side of window openings on inside mount unless other clearance is indicated.

- 
- 3.03 **CLEANING** It is recommended to keep Provident blinds clean and free of dust, they be dusted with a soft non-abrasive cloth, or they may be vacuumed periodically using a hose and soft brush attachment. Clean soiled blind surfaces with a mild soap solution. Do not use steam, hot water, bleach, or any caustic, abrasive or solvent based cleaners or this will void all warranties.

---

### 3.04 HORIZONTAL BLIND SCHEDULE

- A. Provide blinds at the following locations: Listing blind locations, different options, types, accessories and colors.



"Buying American just got easier"



119 Perma R Road • Johnson City, TN 37604  
(800) 552-5278 • Fax (866) 926-5836  
Email: [customerservice@cacoinc.com](mailto:customerservice@cacoinc.com)  
[www.cacoinc.com](http://www.cacoinc.com)