

Specifications

 **GreenScreen Revive®** by


 P.O. Box 5547 • Johnson City, TN 37604-5638

Product Type: Interior - Translucent










Composition: 100% Polyester / PVC Free
 89% Recycled Content

Standard Packaging: Rolls of 50 ly (46 lm)

Width: 118" (300 cm)

Weight: 1% = 5.87 oz / yd² (199 g / m²) ± 5%
 5% = 5.01 oz / yd² (170 g / m²) ± 5%

Thickness: 1% = 0.019" (0.49 mm) ± 5%
 5% = 0.017" (0.44 mm) ± 5%

Color #	Color:	Ts		Rs		As		Tv		CL-S		DG	
		1%	5%	1%	5%	1%	5%	1%	5%	1%	5%	1%	5%
00.02	 White	28	38	66	56	6	6	27	37	0.36	0.44	0.36	0.39
00.10	 Sand	26	35	61	54	13	11	23	33	0.39	0.44	0.37	0.40
00.15	 Dusk	14	22	36	31	50	47	2	8	0.52	0.56	0.45	0.47
00.20	 Linen	25	32	58	52	17	16	20	28	0.41	0.45	0.38	0.41
00.22	 Stone	24	27	52	49	24	24	17	20	0.44	0.46	0.40	0.41
00.55	 Mushroom	20	27	46	42	34	31	10	18	0.47	0.50	0.42	0.44
00.71	 Suede	19	25	39	35	42	40	7	13	0.51	0.54	0.44	0.46
00.01	 Pewter	19	26	43	37	38	37	8	14	0.49	0.53	0.43	0.45
00.30	 Onyx	17	22	34	31	49	47	5	9	0.54	0.56	0.46	0.47

*The fenestration property tests were conducted in accordance with EN 14501:2005, ASTM 891, ASTM E903-96: Shading Coefficient (SC), Solar Heat Gain Coefficient (SHGC), Solar Transmittance (Ts), Solar Reflectance (Rs), Solar Absorptance (As), Visible Light Transmittance (Tv); ¼ (6mm) Clear Glass (CL); 4mm Clear Glass, Single Glazing (CL-S); Double Glazing 4mm/16mm/4mm with low E-coating in position 3, space filled with Argon (DG); To calculate shading coefficient: SHGC CL-S / 0.87. Acoustical performance tested in accordance with ASTM C423-09a: NRC is Noise Reduction Coefficient, SAA is Sound Absorption Average. The above data is indicative.



Fabrication Methods*:

Cutting: cold, ultrasonic or crush

Welding: radio frequency, high frequency, impulse, hot air, hot wedge.

May require the use of welding tape.

Fire Classifications:

NFPA 701-04TM#1, California U.S. Title 19

Fungal Resistance:

ASTM G21

Environmental Benefits:

RoHS - Lead Free, PVC Free

Acoustical Performance:

1% = NRC: 0.25, SAA: 0.24*We recommend testing all cutting and welding methods prior to use to confirm they meet your individual fabrications specifications.

Care and Cleaning:

Regular light dusting with a feather duster is suggested. A hand-held vacuum with low suction may also be used. When vacuuming, avoid pulling or stretching the fabric.

Rigorous vacuuming is not recommended since this could distort the fabric. Alternatively, dirt and debris can be blown away using compressed air or a hand-held hair dryer on the cool setting.



GreenScreen®
Revive has been
certified for its material
content, recyclability,
and manufacturing
characteristics.
c2ccertified.com

